



# Matrox Meteor-II/1394 >>

IEEE 1394-to-PCI adapter board for digital video acquisition.



## Key features

- ▶ three 400 Mbps IEEE 1394 ports
- ▶ extensive FIFO for reliable capture to PC
- ▶ power for IEEE 1394 drawn directly from PC power supply
- ▶ supports IEEE 1394 video cameras based on the IIDC Digital Camera Specification using Matrox Imaging Library (MIL)
- ▶ programmed using Matrox Imaging Library (MIL) sold separately
- ▶ supports 32/64-bit Microsoft® Windows® XP/Vista® through MIL

## Simplified, High-performance Digital Video Capture

Matrox Meteor-II/1394 is an IEEE 1394-to-PCI adapter board for simplified, high-performance digital video capture using a PC. Connect a new generation of industrial/scientific video cameras to a PC using the industry standard IEEE 1394 serial link. Offering functionality equivalent to existing cameras, IEEE 1394-based cameras provide higher-quality video than their analog counterparts and simpler cabling than traditional digital cameras, making them ideal for machine vision, medical imaging and security applications. Matrox Meteor-II/1394, through Matrox Imaging Library (MIL), fully supports IEEE 1394 video cameras based on the IIDC Digital Camera Specification for companies such as Basler and Sony.

### IEEE 1394 digital video

The high speed IEEE 1394 digital serial link supports data transfer rates of 100, 200 and 400 Mbps, meeting the bandwidth demands of typical video resolutions and frame rates. It supports bi-directional communication for device control and transfer of device data such as video, as well as provides support for two types of data transfer modes depending on the nature of the data. Asynchronous data transfer mode provides guaranteed delivery of control commands. Isochronous data transfer mode provides guaranteed bandwidth for time-critical data such as live video.

IEEE 1394 simplifies camera interfacing with a standard connector and cable design that provides video transmission, camera control and power to the camera over a single cable. There is no need to use a specialized frame grabber that requires custom cables and software drivers.



### IEEE 1394 to PCI

Matrox Meteor-II/1394 adapter board provides three external 6-pin IEEE 1394 ports. It is based on a Texas Instruments® chipset which integrates a deep FIFO for reliable video capture and transfer over the PCI bus. Power supplied through the IEEE 1394 connector is drawn directly from the PC power supply and not the PCI slot.

### Field-proven application development software

Matrox Meteor-II/1394 is supported by the Matrox Imaging Library (MIL), a comprehensive collection of software tools for developing industrial imaging applications. MIL features interactive software and programming functions for image capture, processing, analysis, annotation, display and archiving. These tools are designed to enhance productivity, thereby reducing the time and effort required to bring your solution to market. Refer to the MIL datasheet for more information.

## Specifications

### Hardware

- three 6-pin 400 Mbps IEEE 1394 ports
- Texas Instruments physical/link layer chipset (OHCI compliant)
- 8 KB FIFO (4KB for isochronous, 2KB for asynchronous receive and 2KB for asynchronous transmit)
- 32-bit/33 MHz PCI 2.2 bus interface
- power for IEEE 1394 drawn directly from PC power supply
- universal PCI card edge connector

### Software Drivers

- Matrox Imaging Library (MIL) drivers for 32/64-bit Microsoft® Windows® XP/Vista®

### Dimensions and environmental information

- 12.0 cm L x 10.6 cm H (4.7" L x 4.2" H)<sup>1</sup>
- operating temperature: 0° C to 55° C (32° F to 131° F)
- relative humidity: up to 95% (non-condensing) over board(s)
- FCC class A
- CE class A

### Corporate headquarters:

Matrox Electronic Systems Ltd.  
1055 St. Regis Blvd.  
Dorval, Quebec H9P 2T4  
Canada  
Tel: +1 (514) 685-2630  
Fax: +1 (514) 822-6273

## Ordering Information

### Hardware

Part number	Description
METEOR2-1394	Matrox Meteor-II IEEE 1394-to-PCI adapter board.

### Software

Refer to MIL datasheet.

### Notes:

1. Vertical dimensions are from bottom edges of goldfinger to top edge of board. Horizontal dimensions are from edges of the board excluding bracket.
2. Contact local representative or Matrox Imaging Sales for availability.

For more information, please call: 1-800-804-6243 (toll free in North America) or (514) 822-6020  
or e-mail: [imaging.info@matrox.com](mailto:imaging.info@matrox.com) or <http://www.matrox.com/imaging>

**matrox**®

All trademarks by their respective owners are hereby acknowledged. Matrox Electronic Systems, Ltd. reserves the right to make changes in specifications at any time and without notice. The information furnished by Matrox Electronic Systems, Ltd. is believed to be accurate and reliable. However, no responsibility license is granted under any patents or patent rights of Matrox Electronic Systems, Ltd. Windows and Microsoft are trademarks of Microsoft Corporation. MMX and the MMX logo are registered trademarks of Intel Corporation. Printed in Canada, 2009-02-17. **51E-5137-D**